

August 9, 2017

I-94 Interchange to Watford City Bypass (McKenzie County Road 30) Project 9-085(085)075 PCN 20046 • Stark, Billings and McKenzie Counties, North Dakota












- Expand US Highway 85 to four lanes (with flexible design options to avoid or minimize impacts)
- Rehabilitate or replace the historic Long X Bridge over the Little Missouri River
- > EIS
 - Lead agencies: FHWA & NDDOT
 - Cooperating Agencies: NPS, USACE, USFS







Long X Bridge

- › Historic Bridge
- > Constraints
- > Three Alternatives Under Consideration:
 - Increase Vertical Clearance (Rehab) & Construct New Two-Lane Bridge Adjacent
 - Retain Existing Bridge for Alternate Use & Construct Four-Lane Bridge Adjacent
 - Remove & Replace Existing Bridge with New Four-Lane Bridge

Increase Vertical Clearance & Construct New Two-Lane Bridge Adjacent



Approach view: Increase Vertical Clearance & Construct New Two-Lane Bridge Adjacent



Aerial view: Increase Vertical Clearance & Construct New Two-Lane Bridge Adjacent



Retain Existing Bridge for Alternative Use & Construct Four-Lane Bridge Adjacent



Approach view: Retain Existing Bridge for Alternative Use & Construct Four-Lane Bridge Adjacent



Aerial view: Retain Existing Bridge for Alternative Use & Construct Four-Lane Bridge Adjacent



Remove & Replace Existing Bridge with New Four-Lane Bridge



Approach view: Remove & Replace Existing Bridge with New Four-Lane Bridge



Aerial view: Remove & Replace Existing Bridge with New Four-Lane Bridge





- Bridge superstructure supported by driven pile system and/or drilled shaft system
- > Total of 5 piers
 - 2 on south bank
 - 2 in the river channel
 - 1 on the north bank
- Cofferdams or earthen ring dike
- Causeway or bypass river flow would be maintained by the installation of temporary culverts or leaving part of the channel open





Construction Methods - Rehabilitation

- > Perform modifications to the truss portals and install strengthening plates on the truss members
- Remove the existing deck and traffic barriers and install shear studs on the existing stringers
- > Bridge would be contained, sandblasted and repainted
- > Pour the new deck, install the new expansion joints, traffic barriers and guardrail



Demolition

- > Bridge deck would likely be sawed into pieces using a concrete saw and loaded onto trucks for disposal
- Shield system installed below the deck prevent debris from falling into the water during sawing operation
- > Use of shaped charges for the demolition of the steel superstructure
 - Dropped in water, all components removed and loaded onto trucks for disposal
- All piers and abutments would be removed to a depth of 1-foot below the river bottom and no debris would be allowed to remain in the river channel
- > Shaped charges or conventional construction equipment will be used to remove the piers

Staging Areas

Construction Easements for Long X Bridge Options

